can-am. **COMMANDER MAX XT 1000R**

HIGHLIGHTS

PERFORMANCE • Proven Rotax engine • Dependable drivetrain • Sport segment worthy suspension WORKABILITY Rugged taskmaster Work oriented functionality Vehicle protection and rigidity **DESIGN &** • Interior focused on comfort Superior fit and finish
 Low cost of ownership **ERGONOMICS** PLATFORM **FEATURES**

120.6 in. (306.3 cm) wheelbase
13 in. (33 cm) of ground clearance
15 in. (33.1 cm) suspension travel
2,000 lb (907.2 kg) towing capacity
Dynamic Power Steering (DPS™)
√Isco-Lok† Œ front differential
SPORT/ECO™ modes
RF D.E.S.S. with Start / Stop button
Full roof
Premium half doors

Premium half doors

Mudguards

· Rear differential with Turf mode

SPECIFIC TO XT PACKAGE

• 64 in. (162.6 cm) wide with Arched A-arm 28 in. (71.1 cm) XPS Trail King tires

14 in. (35.6 cm) cast-aluminum wheels

XT front bumper

4,500 lb (2,041 kg) winch

7.6 in. (19.3 cm) digital display with keypad

Can-Am LED signature

F	N	G	T	N	F

Туре	75 kW (100 hp), Rotax® 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L/ H / N / R / P
Drive Train	Selectable Turf Mode / 2WD / 4WD with Visco-Lok† QE auto-locking front differential
Driving Assistance	Electronic Hill Descent Control SPORT / ECO™ modes
Power Steering	Dynamic Power Steering (DPS™)

SUSPENSIONS

Front Suspension	Arched double A-arm with sway bar / 15 in. (38.1 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	Arched TTA with sway bar / 15 in. (38.1 cm) travel
Rear Shocks	Twin tube gas charged shocks

TIRES / WHEELS

Front Tires	XPS Trail King 28 x 9 x 14 in. (71.1 x 22.9 x 35.6 cm)
Rear Tires	XPS Trail King 28 x 11 x 14 in. (71.1 x 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum

BRAKES

Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers



Estimated Dry Weight *	1,930 lb (875.4 kg)
Chassis / Cage	Profiled cage. ROPS approved
LxWxH	160.4 x 64 x 76.2 in (407.3 x 162.6 x 193.5 cm)
Wheelbase	120.6 in. (306.3cm)
Ground Clearance	13 in (33 cm)
Cargo Box Dimension	29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)
Cargo Box Capacity	600 lb (272.2 kg)
Towing Capacity	2000 lb (907.2 kg)
Payload Capacity	1280 lb (580.6 kg)
Storage Capacity	Total: 8.5 gal (32.1 L) Glove Box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (15.1 L) Center console and Cup holders: 0.8 gal (3.1 L) Rear console and Cup holders: 1.2 gal (4.5 L) Side Cargo Box storage (passenger side): 1.6 gal (5.9 L) Dual-side panel storage: 0.8 gal (3.0 L)

Fuel Capacity 10 gal (38 L)

FEATURES

Gauge	7.6 in. (19.3 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT / ECO modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature
Instrumentation	Lighter type DC outlet in console (10-A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Magneto	650-W
Lighting	Two 55 W reflectors headlights with unique Can-Am LED signature and LED tail lights
Winch	4,500 lb (2,041 kg) winch with roller fairlead
Steering Wheel	Adjustable tilt steering
Protection	Full roof Premium half doors Full skid plate Mudguards XT front bumper
Hitch Type	2-in hitch receiver

WARRANTY & EXTENDED SERVICE

Factory warranty 2-year BRP limited warranty	
--	--



