

HIGHLIGHTS

PERFORMANCE	<ul style="list-style-type: none"> • Proven Rotax engine • Dependable drivetrain • Sport segment worthy suspension
WORKABILITY	<ul style="list-style-type: none"> • Rugged taskmaster • Work oriented functionality • Vehicle protection and rigidity
DESIGN & ERGONOMICS	<ul style="list-style-type: none"> • Interior focused on comfort • Superior fit and finish • Low cost of ownership
PLATFORM FEATURES	<ul style="list-style-type: none"> • 90.6 in. (230.1 cm) Wheelbase • 13 in. (33 cm) of ground clearance • 15 in. (38.1 cm) suspension travel • 2,000 lb (907.2 kg) towing capacity • Dynamic Power Steering (DPS™) • Visco-Lok† QE front differential • SPORT / ECO™ modes • RF D.E.S.S. with Start / Stop button • Premium half doors • Mudguards • Rear differential with Turf mode
SPECIFIC TO XT PACKAGE	<ul style="list-style-type: none"> • 64 in. (162.6 cm) wide with Arched A-arm • 28 in. XPS Trail King tires • 14 in. cast-aluminum wheels • XT front bumper • 4,500 lb (2,041 kg) winch • Full roof • 7.6 in. digital display with keypad • Can-Am LED signature



Oxford Blue

ENGINE

Type	75 kW (100 hp), Rotax® 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Selectable Turf Mode / 2WD / 4WD with Visco-Lok† QE auto-locking front differential
Driving Assistance	Electronic Hill Descent Control SPORT / ECO™ modes
Power Steering	Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Arched double A-arm with sway bar / 15 in. (38.1 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	Arched TTA with sway bar / 15 in. (38.1 cm) travel
Rear Shocks	Twin tube gas charged shocks

TIRES / WHEELS

Front Tires	XPS Trail King 28 x 9 x 14 in. (71.1 x 22.9 x 35.6 cm)
Rear Tires	XPS Trail King 28 x 11 x 14 in. (71.1 x 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum

BRAKES

Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers

DIMENSIONS / CAPACITIES

Estimated Dry Weight *	1675 lb (759.8 kg)
Chassis / Cage	Profiled cage. ROPS approved
L x W x H	130 x 64 x 74 in (330.2 x 162.6 x 188.3 cm)
Wheelbase	90.6 in. (230.1 cm)
Ground Clearance	13 in (33 cm)
Cargo Box Dimension	29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)
Cargo Box Capacity	600 lb (272.2 kg)
Towing Capacity	2000 lb (907.2 kg)
Payload Capacity	1030 lb (467.2 kg)
Storage Capacity	Total: 7.3 gal (27.6 L) Glove Box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and Cup holders: 0.8 gal (3.1 L) Side Cargo Box storage (passenger side): 1.6 gal (5.9 L) Dual-side panel storage: 0.8 gal (3.0 L)
Fuel Capacity	10 gal (38 L)

FEATURES

Gauge	7.6 in. (19.3 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT / ECO modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature
Instrumentation	Lighter type DC outlet in console (10-A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Magneto	650-W
Lighting	Two 55 W reflectors headlights with unique Can-Am LED signature and LED tail lights
Winch	4,500 lb (2,041 kg) winch with roller fairlead
Steering Wheel	Adjustable tilt steering
Protection	Premium half doors Full skid plate Mudguards XT front bumper Full roof
Hitch Type	2-in hitch receiver