

HIGHLIGHTS

HIGHLIGHTS	
DEFIANT	Trademark Can-Am DNA with next generation design Low seating position Ergo-Lok cockpit with four way adjustable seats
POWERFUL	120 hp turbocharged Rotax® ACE engine Advanced airflow dynamics QRS-X transmission
PRECISE	TTX suspension with industry leading travel Ultra efficient and lightweight chassis Sharpest handling features
PLATFORM FEATURES	• 64 in. (162.5 cm) wide • 102 in. (259.1 cm) wheelbase • 14 in. (35.6 cm) of ground clearance • High torque Dynamic Power Steering (DPS™) • 20 in. (50.8 cm) suspension travel • FOX 2.5 PODIUM QS3 Piggyback shocks • 14 in. (35.6 cm) aluminum wheels • 30 in. (76.2 cm) Maxxis Carnivore† tires • 4.5 in. (11.4 cm) digital display with keypad • Rear tow hook



- 141	N	INI

Туре	89 kW (120 hp), Rotax® ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled and high- perfomance air filter
Fuel Delivery System	Intelligent Throttle Control (ITC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R / P
Drive Train	Lockable front differential with exclusive Smart- Lok* technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL *Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)
CHEDENICIONIC	

SUSPENSIONS


SUSPENSIONS	
Front Suspension	Double A-arm with sway bar / 20 in. (50.8 cm) travel
Front Shocks	FOX 2.5 PODIUM Piggyback with QS3 compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar / 20 in. (50.8 cm) travel
Rear Shocks	FOX 2.5 PODIUM Piggyback with QS3 compression adjustment and bottom-out control

TIRES / WHEELS

Front Tires	Maxxis Carnivore 30 x 10 x 14 in. (76.2 x 25.4 x 35.6 cm)
Rear Tires	Maxxis Carnivore 30 x 10 x 14 in. (76.2 x 25.4 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum

BRAKES

Front	Dual 262 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm disc brakes with hydraulic twin-piston calipers



DIMENSIONS / CALACITIES	
Estimated Dry Weight *	1,546 lb (701.3 kg)
Chassis / Cage	Dual-phase 980 steel
LxWxH	132 x 64 x 65.4 in. (335.3 x 162.5 x 166.1 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	14 in. (35.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)
Fuel Capacity	10.5 gal (40 L)

	GIOVE BOX. 1:0 gai (0.2 L)
	Central console: 0.8 gal (2.8 L)
	Cup holders: 0.1 gal (0.4 L)
Fuel Capacity	10.5 gal (40 L)
FEATURES	
Gauge	4.5 in. (11.4 cm) wide digital display with
	keypad:
	Speedometer, tachometer, odometer, trips
	and hour meters, fuel, gear position, SPORT /
	ECO™ mode, seat belt and 4 x 4 indicator, front
	and rear diff lock indicators, diagnostics, clock,
	battery voltage, engine temperature, DPS™
	mode
Instrumentation	Lighter type DC Outlet in central console
Magneto	650 W
Anti-theft System	RF Digitally Encoded Security System
· · · · · · · · · · · · · · · · · · ·	(D.E.S.S.™) with Start / Stop button
Lighting	LED headlights and tail lights
Winch	N/A
Protection	Integrated front bumper
	Quarter-doors
	HMWPE full skid plate
	Rear tow hook

WARRANTY

Factory warranty	2-year BRP limited warranty



