Can-am. **MAVERICK X rs TURBO RR** WITH SMART-SHOX

manelanio	
DEFIANT	Trademark Can-Am DNA with next generation design Low seating position Ergo-Lok cockpit with four way adjustable seats
POWERFUL	 Industry leading 195 hp turbocharged and intercooled Rotax® ACE engine Advanced airflow dynamics QRS-X transmission
PRECISE	TTX suspension with industry leading travel Ultra efficient and lightweight chassis Sharpest handling features
PLATFORM FEATURES	 72 in. wide 102 in. wheelbase 16 in. of ground clearance High torque Dynamic Power Steering (DPS) Up to 24 in. suspension travel Rear tow hook
SPECIFIC TO X rs SAS PACKAGE	 195hp Turbo RR engine Smart-Lok^{TWM} front differential Smart-Shox** Technology featuring DDA Valve FOX† 3.0 PODIUM† shocks with bypass 14 in. aluminum beadlock wheels 30 in. Maxxis Bighorn 2.0 tires 4-point harness with shoulder pads +HMWPE heavy-duty full skid plate Full roof X-package graphics/seats 7.6 in. digital display with keypad Can-Am LED signature Painted color
ENGINE	

195 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with

integrated intercooler and high-perfomance air filter

Intelligent Throttle Control (iTC[™]) with Electronic Fuel Injection (EFI)

Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P

Lockable front differential with exclusive Smart-Lok * technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL *Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry

High torque Tri-Mode Dynamic Power Steering (DPS™)

Double A-arm with sway bar / 22 in. (55.9 cm) travel /

Trophy truck inspired arms

FOX† 2.5 PODIUM† Piggyback with bypass and Smart-Shox** Technology featuring DDA Valve (Dynamic Damping Adjustment)

4-link Torsional Trailing-arm X (TTX) with sway bar / 24 in (61 cm) travel FOX† 3.0 PODIUM† remote reservoir with bypass and Smart-Shox** Technology featuring

DDA Valve (Dynamic Damping Adjustment) **Smart-Shox was developed in conjunction with Tractive Industries, a market leader in the suspension industry



Desert Tan, Carbon Black & Can-Am Red

DIMENSIONS / CAPACITIES

Estimated Dry Weight	1,646 lb (747 kg)
Chassis / Cage	Dual-phase 980 steel
L x W x H	132 x 72.7 x 68.5 in. (335.3 x 184.7 x 174 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	16 in. (40.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ [™] quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)
Fuel Capacity	10.5 gal (40 L)
FEATURES	
FEATURES Gauge Instrumentation	Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT / ECO modes, seat belt and 4 x4 indicator, front and rear diff lock indicators, diagnostics, clock battery voltage, engine temperature, DPS mode, Smart-Shox*
Gauge	Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT / ECO modes, seat belt and 4 x4 indicator, front and rear diff lock indicators, diagnostics, clock battery voltage, engine temperature, DPS mode, Smart-Shox* Suspension Mode
Gauge Instrumentation Anti-theft System	Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT / ECO modes, seat belt and 4 x4 indicator, front and rear diff lock indicators, diagnostics, clock battery voltage, engine temperature, DPS mode, Smart-Shox** Suspension Mode Lighter type DC Outlet in central console RF Digitally Encoded Security System (D.E.S.S.™)
Gauge	Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT / ECO modes, seat belt and 4 x4 indicator, front and rear diff lock indicators, diagnostics, clock battery voltage, engine temperature, DPS mode, Smart-Shox* Suspension Mode Lighter type DC Outlet in central console RF Digitally Encoded Security System (D.E.S.S. ^m) with Start / Stop button LED headlights and tail lights
Gauge Instrumentation Anti-theft System Lighting	Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT / ECO modes, seat belt and 4 x4 indicator, front and rear diff lock indicators, diagnostics, clock battery voltage, engine temperature, DPS mode, Smart-Shox* Suspension Mode Lighter type DC Outlet in central console RF Digitally Encoded Security System (D.E.S.S.™) with Start/ Stop button LED headlights and tail lights with unique Can-Am LED signature

Туре

Fuel Delivery System

Transmission

Drive Train

Power Steering

SUSPENSIONS

Front Suspension

Rear Suspension

Front Shocks

Rear Shocks

TIRES / WHEELS	
Front Tires	Maxxis Bighorn 2.0† 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0† 30 x 11 x 14 in. (76.2 x 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum beadlock

BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers

WARRANTY	

Factory warranty

2-years BRP limited warranty

Quarter-doors Full roof 4-point harness with shoulder pads HMWPE heavy-duty full skid plate Rear tow hook



